

Mod Auth Mellon

Configuration

- Download the Trustelem metadata file.
- Install mod_auth_mellon for Apache Linux (for example **apt install libapache2-mod-auth-mellon** for Ubuntu/Debian). This mod may require activation.
- Execute [the script to create Mellon's data](#). It will create 3 files: key/certificate/metadata, required by Mellon.
- In the metadata file generated previously (.xml), add after the line `<AssertionConsumerService...>`:

```
<NameIDFormat>urn: oasis: names: tc: SAML: 1. 1: nameid- format: emailAddress</NameIDFormat>
```

NameIDFormat" has to be adapted if you use a different one in Trustelem and Mellon.

- Put the 4 previous files (key/certificate/metadata Mellon + metadata Trustelem) in a folder accessible for the Web Server (for example **/etc/apache2/mellon**).
- Complete the settings file of you Web Server (in the Apache folder **sites-available**).
*The following example has to be adapted, it was made for a source folder at the root (/) and with the hostname **localhost**.*

```
<Location />
    Require valid-user
    AuthType "Mellon"
    MellonEnable "auth"
    MellonDefaultLoginPath "/"
    MellonEndpointPath "/endpoint"
    MellonSPentityId "https://localhost"
    &#35; Files generated by the script:
    MellonSPPrivateKeyFile "/etc/apache2/mellon/https_localhost.key"
    MellonSPCertFile "/etc/apache2/mellon/https_localhost.cert"
    MellonSPMetadataFile "/etc/apache2/mellon/https_localhost.xml"
    &#35; Metadata Trustelem:
    MellonIdPMetadataFile "/etc/apache2/mellon/metadata-125021.xml"
</Location>
```

- Set up Trustelem with the following parameters:
 - **EntityID**: put the value of MellonSPentityId defined in the configuration above
 - **AssertionConsumerService**: put the combination

`https://[hostname]/[MellonEndpointPath]/postResponse`

With the previous example, the ACS would be: `https://localhost/endpoint/postResponse`

Notes

- The attributes sent by Trustelem are made available by Mellon under the designation **MELLON_ATTRIBUTE=attribute** (they can be found in PHP under \$_SERVER).
- The name of the attributes can be changed by adding in the location part, the directive: **MellonSetEnvNoPrefix "NAME_ATTRIBUTE" "attribute"**.

Revision #1

Created 1 July 2022 09:01:34 by WALLIX Admin

Updated 1 July 2022 09:18:03 by WALLIX Admin