Pydio

Pydio requires a plugin to enable OpenID Connect authentication.

Download and installation

- Download the plugin here.
- Unpack the archive and move authfront.openid to the plugin directory of your Pydio server (typically: /usr/share/pydio plugins).
- Ensure the plugin files have the correct permissions :

```
chown -R www-data:www-data authfront.openid/
```

- Open your Pydio admin dashboard, find the plugin under Authentication and enable it

Configuration

- Configure the plugin with the following values:
- OpenID Issuer

```
https://mydomain.trustelem.com/app/3XXXXX
```

- OpenID Jwks


```
{"keys":[{"kty":"RSA","use":"sig","kid":"58930","alg":"RS256","n":"03DSSaM_B0G70aclJFw-
QK6HRl9hkFg2W5HKCGuAHm5wt2tP4FcQ8RMtLZ_WsdeFlUe9VdUGfACCSExq32k4XDR0PA5FJ9sE2pfGXIyyUP2drhqDI1
Q754faHPjvkX5niiQkaNFby4HBjvsH6VWVU5PfHoHEeT20qemANWNlrfw8-jkMlN1aioWAuWI9L-
OtGqUHEbZy_zj3GrZrAN7G73rClAtcgsIfeqkg3y5g2p4qRynS_MMmpuYiGz89Hcrr3lS52tKjHATskkII-eA-
_78SB413KVKxRYSK9DjlA-Wm5Ott4AN99d6sVUIj0jp-fWSIueE4zy4OKrrQR91IYQ","e":"AQAB"}]}
```


- OpenID Configuration


```
{"issuer":"https://wallix-
jflacher.trustelem.com/app/384294","authorization_endpoint":"https://wallix-
jflacher.trustelem.com/app/384294/auth","token_endpoint":"https://wallix-
jflacher.trustelem.com/app/384294/token","userinfo_endpoint":"https://wallix-
jflacher.trustelem.com/app/384294/userinfo","jwks_uri":"https://wallix-
jflacher.trustelem.com/app/384294/jwks","end_session_endpoint":"https://wallix-
jflacher.trustelem.com/app/384294/end_session","scopes_supported":["email","family_name","give
```

```
n_name","groups","name","openid","organization","phone","profile","uid"],"response_types_suppo
rted":["code","code id_token","id_token","id_token
token"],"grant_types_supported":["authorization_code","implicit"],"subject_types_supported":["
public"],"display_values_supported":["page"],"claims_supported":["sub","iss","auth_time","acr"
,"name","given_name","family_name","profile","email","locale","phone_number"],"ui_locales_supp
orted":["fr-FR","en-
GB"],"id_token_signing_alg_values_supported":["RS256"],"token_endpoint_auth_methods_supported"
:["client_secret_basic","client_secret_post"]}
```


- OpenID ClientID

```
pydio_client_id
```

Revision #1
Created 1 July 2022 09:07:40 by WALLIX Admin
Updated 24 November 2023 14:49:26 by WALLIX Admin